UNIRASOR LINE REMOVAL MACHINE.



Engine: Kohler 13 HP vertical single cylinder gasoline engine. Smart choke easy

start system. More than enough power to remove profile markings in one

pass.

Transmission: Twin section vee belts to isolate engine shaft from shock.

Grinder : Triple off-set spoke vertical drive axle with twin sealed bearings. 3-off

rotating cutter segment with 18-off tungsten carbie cutters on each

segment. 2-off sealed bearing units in each cutter. Dust suppression

rubber skirt around cutter unit.

Control: Cutter lowering lever mounted on handle bar. Fine depth control mounted

On cutter chassis easily reached from operating position. Fine cut control

For smooth finishing without damage to asphalt.

Chassis : Sturdy 80 x 40 mm steel section with 2-off 200 mm dia. Wheels at front &

2-off 150mm dia, castors at rear.

change without notice. Photographs are only representative.

Safety : Engine speed control & off switch mounted at right hand. Cutter

lower/raise Mounted at left hand. Foot parking lever raises machine at rear

& prevents Movements. Handle bars on anti-vibration rubber units.

Unimark operates on policy of continual research and development, therefore specifications can



Unimark Machines Pvt. Ltd.

Unimark Machines Pvt. Ltd. is known to be a specialist in road marking technology. Having vast experience in this domain, Unimark has supplied Road Marking and Safety products to diverse markets including EU, APAC, USA and Africa.

Range of Products

- Road Marking Machines
- Drying Machines
- Preheaters
- Line Removers
- Accessories

Contact Information

Unimark Machines Private Limited.

1st Floor, 'Saraf Court',

Dhantoli, Nagpur-440012,

Maharashtra, INDIA

Phone # 0091-712-6603671-678,

6615768, 2461111

Fax # 0091-712-6603679

 ${\bf Email: info@unimark machines.com}$

Web: www.unimarkmachines.com